

Testing of Beam-to-RHS Column Connections Without Weld-access Holes

K. Miura, Y. Makino* and Y. Obukuro
Kumamoto University, Kumamoto, Japan

Y. Kurobane
Sojo University, Kumamoto, Japan

G. J. van der Vegte
Delft University of Technology, Delft, The Netherlands

M. Tanaka
Tanaka Steelworks Ltd., Kumamoto, Japan

K. Tokudome
Space and Urban Design Office, Kumamoto, Japan

ABSTRACT

This paper presents 3 full-scale tests of beam-to-RHS column connections without weld-access holes. The aim of the tests was to investigate the plastic deformation capacity and ultimate strength of these types of beam-to-column connections. The ultimate moment capacities of the welded beam-to-column connections were predicted by simple formulas based on elementary plastic analysis. In all the specimens, the connections had sufficient overstrength to allow formation of plastic hinges at the beam ends, although one specimen failed through brittle fracture starting from the toe of the weld between the beam flange and the horizontal haunch.

NOMENCLATURE

A_w : cross-sectional area of beam web
 b_b : width of beam flange
 b_c : width of column
 d_j : inner distance between top and bottom diaphragm
 E : elastic modulus
E.L. : elongation
 G : shear modulus of elasticity
 H_b : height of beam
 H_d : outer distance between top and bottom diaphragm
 I : moment of inertia
 j_b : distance between centroids of beam flange
 L : distance between loading point and column face
 l_e : effective weld length
 L_{haunch} : length of haunch
 L_{fracture} : length of fracture path
 $M_{f,u}$: ultimate moment carried by beam flange
 M_m : moment at column face
 M_{max} : maximum moment
 M_p : full plastic moment of beam
 M_u : ultimate moment of beam-to-column connection
 $M_{w,u}$: ultimate moment carried by beam web connection
 S_h : space between edge of diaphragm and beam flange

S_r : vertical space of beam cope
 t_c : thickness of column
 t_d : thickness of diaphragm
 t_f : thickness of beam flange
 t_{pl} : thickness of flange plate
 t_s : thickness of shear tab
 u_1, u_2 : horizontal displacements
 v_1, v_2 : vertical displacements
Y.R. : yield ratio
 $Z_{w,pe}$: plastic modulus of effective cross-section of beam web
 α : ratio of M_{max} and M_p
 η : cumulative plastic deformation factor
 $\sigma_{c,y}$: yield strength of column material
 $\sigma_{f,u}$: ultimate tensile strength of beam flange material
 $\sigma_{s,y}$: yield strength of shear tab material
 $\sigma_{s,u}$: ultimate tensile strength of shear tab material
 θ_m : rotation of connection between beam and column
 θ_p : elastic beam rotation at M_p

INTRODUCTION

Both the 1994 Northridge and 1995 Hyogoken Nanbu (Kobe) earthquakes took structural engineering professionals by surprise in that many of the welded connections in modern steel-building frames showed brittle fractures. Before these earthquakes, engineers commonly assumed that the connections between the beam flanges and columns using complete joint penetration (CJP) groove welds satisfied overstrength criteria to allow formation of plastic hinges in beams (CEN 1994, ICBO 1994). These fractures most frequently occurred in regions around the beam bottom flange groove welds. In Northridge, brittle fractures initiated at a very low level of plastic demand and, in some cases, while structures remained nearly elastic. In Kobe, however, the majority of

*ISOPE Member.

Received November 28, 2001; revised manuscript received by the editors June 26, 2002. The original version (prior to the final revised manuscript) was presented at the 11th International Offshore and Polar Engineering Conference (ISOPE-2001), Stavanger, Norway, June 17–22, 2001.

KEY WORDS: Beam-to-column connection, cyclic load, field welding, full-scale test, seismic design, tubular steel structure, weld-access hole.