

The Effect of Rotor Blade Sweep on the Performance of the Wells Turbine

M. Webster
 Coventry University
 Coventry, United Kingdom

L.M.C. Gato
 Instituto Superior Técnico
 Lisbon, Portugal

ABSTRACT

An experimental investigation into the effect of rotor blade sweep on the performance of the Wells turbine is presented. The blades tested included two sets of symmetrical constant chord NACA 0015 blades: one set had a 30-degree backward sweep, whilst the other was unswept. The aim of the experiments was to investigate and compare the aerodynamic performance of the backward swept and unswept blades for two different rotor solidities. It was expected that the sweep of the blade would significantly alter the pressure distribution around the profile, so as to increase the critical Mach number. The turbine models were also fitted with guide vanes to investigate its effect on the overall turbine performance.

KEY WORDS: Wells turbine, wave energy, turbomachinery, blade sweep

NOMENCLATURE

c	blade chord
Ma	Mach number
p	pressure
Δp_0	energy available to the turbine per unit volume fluid
Δp_0^*	$\Delta p_0 / (\rho \omega^2 R^2)$
Q	volume flow rate
(r, θ, x)	cylindrical coordinate system
r	r/R
R	outer radius
Re	Reynolds number
S	solidity, total blade area/annular area
T	torque
T^*	$T / (\rho \omega^2 R^5)$
U	inlet flow (average) velocity
U^*	$U / (\omega R)$, flow rate coefficient
V	absolute velocity
α	angle of absolute velocity

η	turbine efficiency
ρ	density
ω	rotor angular speed

Subscripts

x, θ	axial, tangential velocity component
0, 1, 2, C	far upstream (in atmosphere), upstream of rotor, downstream of rotor, inside the plenum chamber

Superscripts

*	dimensionless value
---	---------------------

INTRODUCTION

The Wells turbine is an axial flow air turbine designed to equip wave energy extraction devices, particularly the oscillating water column (OWC). The turbine is self-rectifying; i.e. it can produce a unidirectional time averaged torque from a reciprocating flow. Several versions of the turbine have been considered and studied with and without guide vanes; e.g. the monoplane, the biplane, the contra-rotating and the variable pitch Wells turbines (Raghunathan et al., 1981; 1983; 1995; Gato and Falcão, 1988, 1990; Gato et al., 1991, 1996; Beattie and Raghunathan, 1993; Curran and Gato, 1997; Sarmiento et al., 1990; Inoue et al., 1986; Kaneko et al., 1991; White, 1981).

As in wings of high subsonic Mach number aircraft, unwanted compressibility effects may occur at the turbine rotor blades, and limit the blade tip velocity and rotational speed (thus preventing reductions in turbine and generator size) in the same way as they limit commercial aircraft speed. Such effects can be reduced by sweep (virtually all high-subsonic-Mach-number aircraft have swept-back wings). Furthermore, the requirement of the variable-pitch turbine to have a stable rotor-blade pitch torque is accomplished by designing the blades with the pressure centre a little aft of the blades' rotation axis (Taylor and Salter, 1996). This might be easily achieved by sweeping back the blades, Fig. 1.

Flow visualization on a rotor with blades of several plan forms indicates that blade sweep has a large effect on the boundary layer separation at the